STEFAN CEL MARE UNIVERSITY of SUCEAVA, ROMANIA FACULTY of MECHANICAL ENGINEERING, MECHATRONICS AND MANAGEMENT MECHANICAL & TECHNOLOGY DEPARTMENT

TEHNOMUS

NEW TECHNOLOGIES AND PRODUCTS IN MACHINE MANUFACTURING TECHNOLOGIES

Journal





THE 18th INTERNATIONAL CONFERENCE

NEW TECHNOLOGIES AND PRODUCTS IN MACHINE MANUFACTURING TECHNOLOGIES



The articles in this journal have been selected by the Scientific Committee from those presented at

The 18th International Conference TEHNOMUS

New Technologies and Products in Machines Manufacturing Technologies,

Organized by:

Mechanical and Technology Department
Faculty of Mechanical Engineering, Mechatronics and Management
"Stefan cel Mare" University of SUCEAVA

with the assistance of:

The National Authority for Scientific Research Bucharest – ANCS TEHNOMUS Association, Suceava, Romania S.C. SIDEM S.R.L. Suceava, Romania

8 - 9, May 2015, Suceava, ROMANIA

INTERNATIONAL SCIENTIFIC COMMITTEE

António Gonçalves Coelho, Portugal Akhloufi Moulay, Canada Amarandei Dumitru, Romania Cerlincă Delia, Romania Certan Valeriu, Rep. Moldova Doicin Cristian, Romania Fabre Agnès, France Fetecău Cătălin, Romania Georgescu Lucian, Romania Glovnea Marilena, Romania Henry Sebastien, France Ionescu Nicolae, Romania Ionescu Romeo, Romania Javorova Juliana, Bulgary Jobst Gorne, Germany Jos Vander Sloten, Belgium Juwet Mark, Belgium Massenzio Michel, France Mazuru Sergiu, Rep. Moldova

Merckx Dirk, Belgium

Mihai Ioan, Romania Mishev Georgi, Bulgary Muscă Ilie, Romania Nagîţ Gheorghe, Romania Nedelcu Dumitru, Romania Olaru Dumitru, Romania Oprisan Cezar, Romania Păstrăv Leonard, Belgium Păunoiu Viorel, Romania Ramalho Mario, Portugal Sarafis Ilias, Greece Schnakovszky Carol, Romania Seghedin Nicolae, Romania Severin Lucian, Romania Slatineanu Laurențiu, Romania Stareţu Ionel, Romania

Ţierean Mircea Horia, Romania Velicu Ștefan, Romania Vida-Simiti Ioan, Romania Wolff Valery, France

CONTENT:

1.	PROCESS OPTIMIZATION OF A BIOSOURCED COMPOSITE MADE OF FLAX FIBER AND POLYAMIDE 11 Yann Lebaupin, Michael Chauvin, Thuy Quynh Truong Hoang, Fabienne Touchard,	13
	Alexandre Beigbeder	
2.	SEQUENCE INFLUENCE OF STRETCHING AND MOMENT APPLIEDS AT BENDING WITH STRETCHING CONCERNING PRECISION OF PIECES	19
	PRODUCED BY COLD PLASTIC DEFORMATION	
	Lucian V. Severin, Traian Lucian Severin	
3.	THE INFLUENCE OF ALUMINUM IN HIGH ENTROPY ALLOY	25
	FeNiCrCuAl	
_	Gheorghe Buluc, Iulia Florea, Adrian Alexandru, Ioan Carcea	• •
4.	THE YOUNG'S MODULUS AND RESIDUAL STRESS OF TINX THIN	29
	FILMS State Constanting on	
5	Stela Constantinescu. EXPERIMENTAL METHOD USED TO DETERMINE MOONEYRIVLIN	34
3.	CONSTANTS FOR RUBBER. PART I	34
	Românu Ionuţ Cristian	
6.	ANALYSIS OF TIN AND TI(C,N) THIN FILMS COATED BY PNCVD	40
٠.	Stela Constantinescu	
7.	SOIL MONITORING OF VANATORI – GALATI REACREATIONAL AREA	45
	Mircea Viorel Dragan	
8.	MATERIALS PROCESSING WITH LASER	49
	Elena Manuela Stanciu, Alexandru Pascu, Georgiana Chisiu, Ionut Claudiu Roata	
9.	STUDIES ON AIR QUALITY MONITORING IN GALATI CITY AREA	53
	Dragan Mircea Viorel	
10.	DISSIMILAR LASER WELDING OF CARBON STEEL AND STAINLESS STEEL	57
11	Elena Manuela Stanciu, Alexandru Pascu, Ionut Claudiu Roata, Mircea Horia Tierean COMPARATIVE STUDY ON THE RHEOLOGICAL BEHAVIOUR OF	61
11.	SOME INDUSTRIAL ECOLOGICAL LUBRICANTS	01
	Iuliana Marlena Prodea, Nicoleta Teodorescu, Mariana Florentina Ștefănescu,	
12	Ancaelena Eliza Sterpu, Cyrille Alode Vodounon RESEARCH REGARDING THE FILTRATION OF POLLUTED AIR FROM	66
12.	AN WORKING ENVIRONMENT USING ULTRASONIC FILTERS Amza Gheorghe	00
13	EXPERIMENTAL STAND FOR THE STUDY OF THE FUNCTIONING OF	72
10.	MAGNETIC LEVITATION VEHICLES	
	Herman M., Ştirbu H., Herman R.	
14.	TECHNIQUE OF MOTOR VEHICLE INDICES CALCULATION WHILE	76
	TRANSITION OF ITS ENGINE FOR OPERATION AT THE MIXTURE OF	
	DIESEL AND BIODIESEL FUELS	
	A. P. Poliakov, O. O. Galushchak, D. O. Galushchak	
15.	THE OPTIMIZATION OF DIRECTING EMPTY WAGONS	82
	Mihaiela Herman , Gabriel-Vasile Ursu-Neamţ, Horea Ştirbu	
16.	THERMAL SHOCK ANALYSIS USING THE FINITE ELEMENT METHOD	89
	FOR A GIVEN SPECIMEN	
17	Alina-Elena Buşaru, Mariana Goran, Gabriel Marius Dumitru STRESS AND DEFORMATION STATES FOR STRAIGHT EDGE AND	94
1/.	CURVED EDGE HELICAL DRILLS	94
	Nicuşor Baroiu, Dan Cătălin Bîrsan	
18	INFLUENCE OF THE MAGNETIC FIELD ON THE DYNAMIC	101
10.	MECHANICAL PROPERTIES OF MAGNETORHEOLOGICAL ELASTOMERS	101
	Petrică-Eduard Chirilă, Doina Boazu, Nicușor Baroiu	

TECHNIQUE OF MOTOR VEHICLE INDICES CALCULATION WHILE TRANSITION OF ITS ENGINE FOR OPERATION AT THE MIXTURE OF DIESEL AND BIODIESEL FUELS

A. P. Poliakov¹, O. O. Galushchak², D. O. Galushchak³

Abstract: The paper considers the technique of calculation of technical, economical and ecological indices of the engine and motor vehicle on the whole in the process of usage of engine supply system with dynamic regulation of percentage composition of diesel and biodiesel fuels in the mixture. Values of fuel mixture burning duration depending on its temperature, percentage composition and cyclic fuel supply are given.

Keywords:, biodiesel, diesel, fuel mixture, dynamic regulation of percentage composition, system of fuel supply.

1. Introduction

One of the key elements for any kind of economic activity is energy branch of national economy. Demand for energy in the countries of the world is constantly growing and such dynamics will remain in the future. Ukraine imports 43% of energy resources from total needs. In recent years the country produced on average four million tons of oil with gas condensate and 18 milliard m³ of natural gas, that equals 10 and 20% of the country needs, correspondingly. One of the largest consumers of liquid oil-based fuels is automobile transport, besides also influences the ecological state of the environment.

In order to decrease the dependence of the state on the imported fuels research aimed at the usage of alternative fuel is carried out. Biodiesel fuel (BF) is one of the promising substitutes of conventional oil-based fuels. Ukraine possesses powerful potential in the sphere of biofuel, in particular, biodiesel fuel, starting from cultivating raw material —up to final product (biodiesel fuel). Raw material

for biodiesel fuel production may be various vegetable oils, rape oil and processed sunflower oil are also available.

As an alternative fuel, biodiesel fuel (BF), obtained from vegetable raw material, can completely replace diesel fuel (DF). Raw material for the production of BF can be cultivated in the country, that is why, usage of biodiesel fuel decreases the dependence of Ukraine on the imported fuel. Nowadays the problem of alternative fuel usage as the fuel for the engines of motor vehicles is the promising direction of research, it enables not only to reduce operation expenses but also decrease the amount of harmful emissions of exhaust gases.

Usage of biodiesel fuel for diesel engines has been studied for many years. In [1-8] the results of the study dealing with the impact on technical, economical and ecological indices of the diesel engine of the usage of pure biodiesel and its mixture with diesel are given. But greater part of studies was carried out using the mixture of diesel and biodiesel fuels with constant percentage composition. Manufactures of motor vehicles [1-2] also

¹ Ukraine, Vinnitsa National Technical University, farv@inmt.vntu.edu.ua

² Ukraine, Vinnitsa National Technical University, galushchak_o@meta.ua

³ Ukraine, Vinnitsa National Technical University, galushchak_d@meta.ua