

# INFORMATYKA AUTOMATYKA POMIARY



[www.e-IAPGOS.pl](http://www.e-IAPGOS.pl)

W GOSPODARCE I OCHRONIE ŚRODOWISKA

ISSN 2083-0157

Kwartalnik Naukowo-Techniczny



1953 - 2023



70 lat

POLITECHNIKI  
LUBELSKIEJ



fol. arch. PL

# 2/2023

## kwiecień – czerwiec

Wydanie pod redakcją naukową  
prof. dr hab. inż. Waldemara Wójcika

# INFORMATYKA AUTOMATYKA POMIARY

W GOSPODARCE I OCHRONIE ŚRODOWISKA  
Informatics Control Measurement in Economy and Environment Protection

p-ISSN 2083-0157, e-ISSN 2391-6761, www.e-iapgos.pl

### EDITOR STAFF ZESPÓŁ REDAKCYJNY

#### Editor-in-Chief Redaktor naczelny

**Paweł KOMADA**

Lublin University of Technology, Lublin, Poland  
p.komada@pollub.pl

#### Deputy Editors Zastępcy redaktora

**Jan SIKORA**

Research and Development Center Netrix S.A.,  
Lublin, Poland sik59@wp.pl

**Dominik SANKOWSKI**

Lodz University of Technology, Lodz, Poland  
dsan@kis.p.lodz.pl

**Paweł FIALA**

Brno University of Technology, Brno, Czech  
Republic fialap@feec.vutbr.cz

**Andrzej SMOLARZ**

Lublin University of Technology, Lublin, Poland  
a.smolarz@pollub.pl

#### Technical Editor Redaktor techniczny

**Tomasz ŁAWICKI**

Lublin University of Technology, Lublin, Poland  
t.lawicki@pollub.pl

#### Statistical Editor Redaktor statystyczny

**Ewa ŁAZUKA**

Lublin University of Technology, Lublin, Poland  
e.lazuka@pollub.pl

### EDITORIAL OFFICE REDAKCJA

#### Redakcja czasopisma

**Informatyka, Automatyka, Pomiary w  
Gospodarce i Ochronie Środowiska**

Katedra Elektroniki i Technik

Informacyjnych

Politechnika Lubelska

ul. Nadbystrzycka 38A, 20-618 Lublin

tel. +48 81 53 84 309,

fax: +48 81 53 84 312

iapgos@pollub.pl

www.e-iapgos.pl

iapgos.pollub.pl

ph.pollub.pl/index.php/iapgos

### PUBLISHER WYDAWCZA

**Politechnika Lubelska**

ul. Nadbystrzycka 38D

20-618 Lublin

tel. +48 81 53 84 100

www.pollub.pl

ph.pollub.pl

### EDITORIAL BOARD KOMITET REDAKCYJNY

#### Editor-in-Chief Redaktor naczelny

**Paweł KOMADA**

Lublin University of Technology, Lublin, Poland  
p.komada@pollub.pl

#### Topical Editors Redaktorzy działowi

##### *Electrical Engineering* *Elektrotechnika*

**Jan SIKORA**

Research and Development Center Netrix S.A.,  
Lublin, Poland sik59@wp.pl

##### *Computer Science* *Informatyka*

**Dominik SANKOWSKI**

Lodz University of Technology, Lodz, Poland  
dsan@kis.p.lodz.pl

##### *Electronics* *Elektronika*

**Paweł FIALA**

Brno University of Technology, Brno, Czech  
Republic fialap@feec.vutbr.cz

##### *Automatic* *Automatyka*

**Waldemar WÓJCİK**

Lublin University of Technology, Lublin, Poland  
waldemar.wojcik@pollub.pl

##### *Environmental Engineering* *Inżynieria środowiska*

**Łucjan PAWŁOWSKI**

Lublin University of Technology, Lublin, Poland  
l.pawlowski@pollub.pl

##### *Mechtronics* *Mechatronika*

**Krzysztof KLUSZCZYŃSKI**

Silesian University of Technology, Gliwice,  
Poland krzysztof.kluszczyński@polsl.pl

### INTERNATIONAL PROGRAMME COMMITTEE RADA PROGRAMOWO- NAUKOWA

#### Chairman

**Przewodniczący**

**Waldemar WÓJCİK**

Lublin University of Technology, Lublin, Poland

#### Deputy of Chairman

**Zastępca przewodniczącego**

**Jan SIKORA**

Research and Development Center Netrix S.A.,  
Lublin, Poland

#### Members

**Członkowie**

**Kazimierz ADAMIAK**

University of Western Ontario, Ontario, Canada

**Darya ALONTSEVA**

D.Serikbaev East Kazakhstan State Technical  
University, Ust-Kamenogorsk, Kazakhstan

**Shin-ichi AOQUI**

Sojo University, Kumamoto, Japan

**Javier BALLESTER**

Universidad de Zaragoza, Saragossa, Spain

**Yurii BOBALO**

Lviv Polytechnic National University, Lviv,  
Ukraine

**Oleksy BORYSENKO**

Department of Electronics and Computer  
Technics, Sumy, Ukraine

**Hartmut BRAUER**

Technische Universität Ilmenau, Ilmenau,  
Germany

**Kathleen CURRAN**

School of Medicine & Medical Science, Dublin,  
Ireland

**Milan DADO**

University of Žilina, Žilina, Slovakia

**Jarmila DEDKOVA**

Brno University of Technology, Brno, Czech  
Republic

**Andrzej DEMENKO**

Poznan University of Technology, Poznań,  
Poland

**Paweł FIALA**

Brno University of Technology, Brno, Czech  
Republic

**Vladimir FIRAGO**

Belarusian State University, Minsk, Belarus

**Ryszard GOLEMAN**

Lublin University of Technology, Lublin, Poland

**Jan GÓRSKI**

AGH University of Science and Technology,  
Cracow, Poland

**Stanisław GRATKOWSKI**

West Pomeranian University of Technology  
Szczecin, Szczecin, Poland

**Antoni GRZANKA**

Warsaw University of Technology, Warsaw,  
Poland

**Jeni HEINO**

Helsinki University of Technology, Helsinki,  
Finland

**Oleksandra HOTRA**

Lublin University of Technology, Lublin, Poland

**Wojciech JARZYNA**

Lublin University of Technology, Lublin, Poland

**Mukhtar JUNISBEKOV**

M.Kh. Dulaty Taraz State University, Taraz,  
Kazakhstan

**Piotr KACEJKO**

Lublin University of Technology, Lublin, Poland

**Krzysztof KLUSZCZYŃSKI**

Silesian University of Technology, Gliwice,  
Poland

**Grzegorz KŁOSOWSKI**

Lublin University of Technology, Lublin, Poland

**Yurii KRAK**Taras Shevchenko National University of Kyiv,  
Kiev, Ukraine**Piotr KSIĄŻEK**

Medical University of Lublin, Lublin, Poland

**Piotr LESIAK**University of Economics and Innovation in  
Lublin Lublin, Poland**Volodymyr LYTUVYENKO**Kherson National Technical University,  
Kherson, Ukraine**Artur MEDVID**

Riga Technical University, Riga, Latvia

**Paweł MERGO**Maria Curie-Skłodowska University, Lublin,  
Poland**Zbigniew OMIOTEK**

Lublin University of Technology, Lublin, Poland

**Andrzej NAFALSKI**University of South Australia, Adelaide,  
Australia**Il Han PARK**

Sungkyunkwan University, Suwon, Korea

**Lucjan PAWŁOWSKI**

Lublin University of Technology, Lublin, Poland

**Sergey PAVLOV**Vinnytsia National Technical University,  
Vinnytsia, Ukraine**Leonid POLISHCHUK**Vinnytsia National Technical University,  
Vinnytsia, Ukraine**Denis PREMEL**

CEA Saclay, Gif-sur-Yvette, France

**Jason RILEY**The Eunice Kennedy Shriver National Institute  
of Child Health and Human Development,  
Bethesda, USA**Ryszard ROSKOSZ**Gdańsk University of Technology, Gdańsk,  
Poland**Tomasz RYMARCZYK**Research and Development Center Netrix S.A.,  
Lublin, Poland**Dominik SANKOWSKI**

Lodz University of Technology, Lodz, Poland

**Stanislav SLOSARCIK**

Technical University of Kosice, Kosice, Slovakia

**Jan SROKA**Warsaw University of Technology, Warsaw,  
Poland**Bohdan STADNYK**Lviv Polytechnic National University, Lviv,  
Ukraine**Henryka Danuta STRYCZEWSKA**

Lublin University of Technology, Lublin, Poland

**Batyrbek SULEMENOV**Kazakh National Research Technical University  
after K.I.Satpayev, Almaty, Kazakhstan**Mirosław ŚWIERCZ**Białystok University of Technology, Białystok,  
Poland**Stanisław TARASIEWICZ**

Université Laval, Quebec, Canada

**Murielle TORREGROSSA**

University of Strasbourg, Strasbourg, France

**Sławomir TUMAŃSKI**Warsaw University of Technology, Warsaw,  
Poland**Oleksandr VASILEVSKYI**Vinnytsia National Technical University,  
Vinnytsia, Ukraine**Andrzej WAC-WŁODARCZYK**

Lublin University of Technology, Lublin, Poland

**Zygmunt WARSZA**Industrial Research Institute for Automation and  
Measurements, Warsaw, Poland**Sotoshi YAMADA**

Kanazawa University, Kanazawa, Japan

**Xiaoyi YANG**

Beihang University, Beijing, China

**Mykola YERMOSHENKO**International Academy of Information Sciences,  
Kiev, Ukraine**Athanasios ZACHAROPOULOS**University College London, London, United  
Kingdom**Ivan ZHARSKI**Belarusian National Technical University,  
Minsk, Belarus**Cao ZHIHONG**Institute of Soil Science Chinese Academy  
of Sciences, Nanjing, China**Paweł ŻUKOWSKI**

Lublin University of Technology, Lublin, Poland

**PRINTING HOUSE – DRUKARNIA****PPH Remigraf Sp. z o.o.**

ul. Dźwigowa 61, 01-376 Warszawa

<https://remigraf.pl/>

nakład: 100 egzemplarzy

**OTHER INFORMATION – INNE INFORMACJE****Czasopismo jest indeksowane w bazach:**

DOAJ	doaj.org
BazTech	baztech.icm.edu.pl
IC Journals Master List	www.journals.indexcopernicus.com
Google Scholar	scholar.google.pl
POL-index	pbn.nauka.gov.pl
Sherpa RoMEO	www.sherpa.ac.uk
OAJI	oaji.net
SCOPUS	www.scopus.com
EBSCO	www.ebsco.com

Czasopismo *Informatyka, Automatyka, Pomiar w Gospodarce i Ochronie Środowiska* zostało objęte finansowaniem przez Ministerstwo Nauki i Szkolnictwa Wyższego w ramach programu *Wsparcie dla czasopism naukowych* w latach 2019-2020.

Czasopismo znajduje się w wykazie czasopism naukowych opublikowanym w Komunikacie Ministra Edukacji i Nauki z dnia 1 grudnia 2021 r., Unikatowy Identyfikator Czasopisma: 200167 – z przypisaną liczbą punktów przyznawanych za publikację artykułu równą 20.

Zasady publikowania artykułów, przygotowania tekstów, zasady etyczne, procedura recenzowania, wykazy recenzentów oraz pełne teksty artykułów dostępne są na stronie internetowej czasopisma:

[www.e-iapgos.pl](http://www.e-iapgos.pl)

W celu zwiększenia oddziaływania czasopisma w środowisku naukowym redakcja zaleca:

- w artykułach publikowanych w IAPGOS cytować artykuły z renomowanych czasopism międzynarodowych (szczególnie indeksowanych w bazach Web of Science oraz Scopus) używając oficjalnych skrótów nazw czasopism,
- w artykułach publikowanych w innych czasopismach (zwłaszcza indeksowanych w bazach Web of Science oraz Scopus) cytować prace publikowane w IAPGOS – zwłaszcza posługując się numerami DOI, np.:  
Kluszczyński K. *Modelowanie – umiejętność czy sztuka?* *Informatyka, Automatyka, Pomiar w Gospodarce i Ochronie Środowiska – IAPGOS*, 1/2016, 4–15, <https://doi.org/10.5604/20830157.1193833>.



## CONTENTS – SPIS TREŚCI

<b>1. Łukasz Maciura, Dariusz Wójcik, Tomasz Rymarczyk, Krzysztof Król</b> Novel hybrid algorithm using convolutional autoencoder with SVM for electrical impedance tomography and ultrasound computed tomography Nowy algorytm hybrydowy wykorzystujący autoenkoder konwolucyjny z SVM dla elektrycznej tomografii impedancyjnej i tomografii ultradźwiękowej.....	4
<b>2. Igor Palamarchuk, Vladyslav Palamarchuk, Vadim Paziuk, Ruslan Hulevych, Aliya Kalizhanova, Magzhan Sarsembayev</b> Analysis of power and energy parameters of the conveyor infrared dryer of oil-containing raw materials Analiza mocy i parametrów energetycznych przenośnikowej, działającej na podczerwień suszarni surowców zawierających olej .....	10
<b>3. Dmytro Milenin, Mykola Lysychenko, Andriy Milenin, Leonid Koval, Saltanat Amirgaliyeva, Maxatbek Satymbekov, Saltanat Adikanova</b> Optimization of resource allocation, exposure time and rotary speed of incubative eggs Optymalizacja alokacji zasobów, czasu ekspozycji i prędkości obrotowej jaj inkubacyjnych .....	15
<b>4. Gulnar Balakayeva, Gaukhar Kalmenova, Dauren Darkenbayev, Chris Phillips</b> Development of an application for the thermal processing of oil slime in the industrial oil and gas sector Opracowanie aplikacji do termicznego przetwarzania szlamów olejowych w przemysłowym sektorze naftowym i gazu.....	20
<b>5. Gregory S. Tymchyk, Volodymyr I. Skytsiuk, Tatiana R. Klotchko, Leonid K. Polishchuk, Anatolii V. Hrytsak, Saule J. Rakhmetullina, Beibut Amirgaliyev</b> Automated definition of the discrete elements interactions in workspace of equipment Automatyczne określanie interakcji elementów dyskretnych w przestrzeni pracy urządzeń .....	27
<b>6. Gregory S. Tymchyk, Volodymyr I. Skytsiuk, Tatiana R. Klotchko, Roman B. Akselrod, Valerii Yo. Shenfeld, Aliya Kalizhanova, Didar Yedilkhan, Gaukhar Borankulova</b> TONTOR zones model for automative object monitoring Model stref TONTOR do automatycznego monitorowania obiektów.....	36
<b>7. Viacheslav Titov, Oleksandr Mozghoyi, Ruslan Borys, Mykola Bogomolov, Yedilkhan Amirgaliyev, Zhalau Aitkulov</b> Theoretical and experimental substantiation of the extraction process with thinning bimetallic tubular elements of dissimilar metals and alloys Teoretyczne i eksperymentalne uzasadnienie procesu ciągnięcia z przerzedzaniem bimetalicznych elementów rurowych z różnych metali i stopów ...	44
<b>8. Achraf Benba, Mouna Akki, Sara Sandabad</b> The application of machine learning on the sensors of smartphones to detect falls in real-time Zastosowanie uczenia maszynowego na czujnikach smartfonów do wykrywania upadków w czasie rzeczywistym.....	50
<b>9. Yosyp Bilynsky, Aleksandr Nikolskyy, Viktor Revenok, Vasyl Pogorilyi, Saule Smailova, Oksana Voloshina, Saule Kumargazhanova</b> Convolutional neural networks for early computer diagnosis of child dysplasia Konwolucyjne sieci neuronowe do wczesnej diagnostyki komputerowej dysplazji u dzieci.....	56
<b>10. Olena Kolesnikova, Olena Vysotska, Anna Potapenko, Anastasia Radchenko, Anna Trunova, Nataliya Virstyuk, Liudmyla Vasylevska-Skupa, Aliya Kalizhanova, Nazerka Mukanova</b> Cardiometabolic risk prediction in patients with non-alcoholic fatty liver disease combined with subclinical hypothyroidism Przewidywanie ryzyka kardiometabolicznego u pacjentów z niealkoholową stłuszczeniową chorobą wątroby w połączeniu z subkliniczną niedoczynnością tarczycy .....	64
<b>11. Leonid Timchenko, Natalia Kokriatskaya, Volodymyr Tverdomed, Natalia Kalashnik, Iryna Shvarts, Vladyslav Plisenko, Dmytro Zhuk, Saule Kumargazhanova</b> Local difference threshold learning in filtering normal white noise Proces uczenia względem lokalnego proggu różnicy w filtrowaniu normalnego szumu białego .....	69
<b>12. Zakir Nasib Huseynov, Mahil Isa Mammadov, Togrul Atabay Ismayilov</b> Modeling and analysis of the characteristics of multichannel and multi-node computer networks with priority service Modelowanie i analiza charakterystyk wielokanałowych i wielowęzłowych sieci komputerowych z usługą priorytetową .....	74
<b>13. Vira Petruk, Olena Prozor, Yuliia Sabadosh, Iryna Baranovska, Maksim Palii, Yevhenia Moroz, Saule Kumargazhanova, Dinara Mussayeva</b> Statistical methods for evaluating experimental data on the use of mathematical competencies in study for a resilient economy Statystyczne metody oceny danych eksperymentalnych dotyczących wykorzystania kompetencji matematycznych w badaniach na rzecz odpornej gospodarki .....	78
<b>14. Olena Liutak, Olena Baula, Anatolii Tkachuk</b> Simulation of the influence of investment and innovation activities on ensuring the international competitiveness of countries Symulacja wpływu działań inwestycyjnych i innowacyjnych na zapewnienie międzynarodowej konkurencyjności krajów .....	86

## CONTENTS – SPIS TREŚCI

<b>1. Łukasz Maciura, Dariusz Wójcik, Tomasz Rymarczyk, Krzysztof Król</b> Novel hybrid algorithm using convolutional autoencoder with SVM for electrical impedance tomography and ultrasound computed tomography Nowy algorytm hybrydowy wykorzystujący autoenkoder konwolucyjny z SVM dla elektrycznej tomografii impedancyjnej i tomografii ultradźwiękowej.....	4 <a href="http://doi.org/10.35784/iapgos.3377">http://doi.org/10.35784/iapgos.3377</a>
<b>2. Igor Palamarchuk, Vladyslav Palamarchuk, Vadim Paziuk, Ruslan Hulevych, Aliya Kalizhanova, Magzhan Sarsembayev</b> Analysis of power and energy parameters of the conveyor infrared dryer of oil-containing raw materials Analiza mocy i parametrów energetycznych przenośnikowej, działającej na podczerwień suszarni surowców zawierających olej .....	10 <a href="http://doi.org/10.35784/iapgos.3487">http://doi.org/10.35784/iapgos.3487</a>
<b>3. Dmytro Milenin, Mykola Lysychenko, Andriy Milenin, Leonid Koval, Saltanat Amirgaliyeva, Maxatbek Satymbekov, Saltanat Adikanova</b> Optimization of resource allocation, exposure time and rotary speed of incubative eggs Optymalizacja alokacji zasobów, czasu ekspozycji i prędkości obrotowej jaj inkubacyjnych .....	15 <a href="http://doi.org/10.35784/iapgos.3494">http://doi.org/10.35784/iapgos.3494</a>
<b>4. Gulnar Balakayeva, Gaukhar Kalmenova, Dauren Darkenbayev, Chris Phillips</b> Development of an application for the thermal processing of oil slime in the industrial oil and gas sector Opracowanie aplikacji do termicznego przetwarzania szlamów olejowych w przemysłowym sektorze naftowym i gazu.....	20 <a href="http://doi.org/10.35784/iapgos.3463">http://doi.org/10.35784/iapgos.3463</a>
<b>5. Gregory S. Tymchyk, Volodymyr I. Skytsiuk, Tatiana R. Klotchko, Leonid K. Polishchuk, Anatolii V. Hrytsak, Saule J. Rakhmetullina, Beibut Amirgaliyev</b> Automated definition of the discrete elements interactions in workspace of equipment Automatyczne określanie interakcji elementów dyskretnych w przestrzeni pracy urządzeń .....	27 <a href="http://doi.org/10.35784/iapgos.3495">http://doi.org/10.35784/iapgos.3495</a>
<b>6. Gregory S. Tymchyk, Volodymyr I. Skytsiuk, Tatiana R. Klotchko, Roman B. Akselrod, Valerii Yo. Shenfeld, Aliya Kalizhanova, Didar Yedilkhan, Gaukhar Borankulova</b> TONTOR zones model for automative object monitoring Model stref TONTOR do automatycznego monitorowania obiektów.....	36 <a href="http://doi.org/10.35784/iapgos.3518">http://doi.org/10.35784/iapgos.3518</a>
<b>7. Viacheslav Titov, Oleksandr Mozghoyvi, Ruslan Borys, Mykola Bogomolov, Yedilkhan Amirgaliyev, Zhalau Aitkulov</b> Theoretical and experimental substantiation of the extraction process with thinning bimetallic tubular elements of dissimilar metals and alloys Teoretyczne i eksperymentalne uzasadnienie procesu ciągnięcia z przerzedzaniem bimetalicznych elementów rurowych z różnych metali i stopów ...	44 <a href="http://doi.org/10.35784/iapgos.3497">http://doi.org/10.35784/iapgos.3497</a>
<b>8. Achraf Benba, Mouna Akki, Sara Sandabad</b> The application of machine learning on the sensors of smartphones to detect falls in real-time Zastosowanie uczenia maszynowego na czujnikach smartfonów do wykrywania upadków w czasie rzeczywistym.....	50 <a href="http://doi.org/10.35784/iapgos.3459">http://doi.org/10.35784/iapgos.3459</a>
<b>9. Yosyp Bilynsky, Aleksandr Nikolskyy, Viktor Revenok, Vasyl Pogorilyi, Saule Smailova, Oksana Voloshina, Saule Kumargazhanova</b> Convolutional neural networks for early computer diagnosis of child dysplasia Konwolucyjne sieci neuronowe do wczesnej diagnostyki komputerowej dysplazji u dzieci.....	56 <a href="http://doi.org/10.35784/iapgos.3499">http://doi.org/10.35784/iapgos.3499</a>
<b>10. Olena Kolesnikova, Olena Vysotska, Anna Potapenko, Anastasia Radchenko, Anna Trunova, Nataliya Virstyuk, Liudmyla Vasylevska-Skupa, Aliya Kalizhanova, Nazerka Mukanova</b> Cardiometabolic risk prediction in patients with non-alcoholic fatty liver disease combined with subclinical hypothyroidism Przewidywanie ryzyka kardiometabolicznego u pacjentów z niealkoholową stłuszczeniową chorobą wątroby w połączeniu z subkliniczną niedoczynnością tarczycy .....	64 <a href="http://doi.org/10.35784/iapgos.3654">http://doi.org/10.35784/iapgos.3654</a>
<b>11. Leonid Timchenko, Natalia Kokriatskaya, Volodymyr Tverdomed, Natalia Kalashnik, Iryna Shvarts, Vladyslav Plisenko, Dmytro Zhuk, Saule Kumargazhanova</b> Local difference threshold learning in filtering normal white noise Proces uczenia względem lokalnego progu różnicy w filtrowaniu normalnego szumu białego .....	69 <a href="http://doi.org/10.35784/iapgos.3664">http://doi.org/10.35784/iapgos.3664</a>
<b>12. Huseynov Zakir Nasib, Mammadov Mahil Isa, Ismayilov Togrul Atabay</b> Modeling and analysis of the characteristics of multichannel and multi-node computer networks with priority service Modelowanie i analiza charakterystyk wielokanałowych i wielowęzłowych sieci komputerowych z usługą priorytetową .....	74 <a href="http://doi.org/10.35784/iapgos.3394">http://doi.org/10.35784/iapgos.3394</a>
<b>13. Vira Petruk, Olena Prozor, Yuliia Sabadosh, Iryna Baranovska, Maksim Palii, Yevheniia Moroz, Saule Kumargazhanova, Dinara Mussayeva</b> Statistical methods for evaluating experimental data on the use of mathematical competencies in study for a resilient economy Statystyczne metody oceny danych eksperymentalnych dotyczących wykorzystania kompetencji matematycznych w badaniach na rzecz odpornej gospodarki .....	78 <a href="http://doi.org/10.35784/iapgos.3504">http://doi.org/10.35784/iapgos.3504</a>
<b>14. Olena Liutak, Olena Baula, Anatolii Tkachuk</b> Simulation of the influence of investment and innovation activities on ensuring the international competitiveness of countries Symulacja wpływu działań inwestycyjnych i innowacyjnych na zapewnienie międzynarodowej konkurencyjności krajów .....	86 <a href="http://doi.org/10.35784/iapgos.3470">http://doi.org/10.35784/iapgos.3470</a>

## CONVOLUTIONAL NEURAL NETWORKS FOR EARLY COMPUTER DIAGNOSIS OF CHILD DYSPLASIA

Yosyp Bilynsky<sup>1,2</sup>, Aleksandr Nikolsky<sup>3</sup>, Viktor Revenok<sup>2,3</sup>, Vasyl Pogorilyi<sup>3</sup>, Saule Smailova<sup>4</sup>, Oksana Voloshina<sup>5</sup>, Saule Kumargazhanova<sup>4</sup>

<sup>1</sup>Vinnitsia National Technical University, Vinnitsia, Ukraine, <sup>2</sup>Vinnitsia National Agrarian University, Vinnitsia, Ukraine, <sup>3</sup>National Pirogov Memorial Medical University, Vinnitsia, Ukraine, <sup>4</sup>D.Serikbayev East Kazakhstan State Technical University, Ust-Kamenogorsk, Kazakhstan, <sup>5</sup>Vinnitsia Mykhailo Kotsubynsky State Pedagogical University, Vinnitsia, Ukraine

**Abstract.** The problem in ultrasound diagnostics hip dysplasia is the lack of experience of the doctor in case of incorrect orientation of the hip joint and ultrasound head. The aim of this study was to evaluate the ability of the convolutional neural network (CNN) to classify and recognize ultrasound imaging of the hip joint obtained at the correct and incorrect position of the ultrasound sensor head in the computer diagnosis of pediatric dysplasia. CNNs such as GoogleNet, SqueezeNet, and AlexNet were selected for the study. The most optimal for the task is the use of CNN GoogleNet showed. In this CNN used transfer learning. At the same time, fine-tuning of the network and additional training on the database of 97 standards of ultrasonic images of the hip joint were applied. Image type RGB 32 bit, 210 × 300 pixels are used. Fine-tuning has been performed the lower layers of the structure CNN, in which 5 classes are allocated, respectively 4 classes of hip dysplasia types according to the Graf, and the Type ERROR ultrasound image, where position of the ultrasound sensor head and of the hip joint in ultrasound diagnostics are incorrect orientation. It was found that the authenticity of training and testing is the highest for the GoogleNet network: when classified in the training group accuracy is up to 100%, when classified in the test group accuracy – 84.5%.

**Keywords:** convolutional neural networks, computer diagnosis, ultrasound image child dysplasia

### KONWOLUCYJNE SIECI NEURONOWE DO WCZESNEJ DIAGNOSTYKI KOMPUTEROWEJ DYSPLAZJI U DZIECI

**Streszczenie.** Problemem w diagnostyce ultrasonograficznej dysplazji stawu biodrowego jest brak doświadczenia lekarzy w zakresie nieprawidłowej orientacji stawu biodrowego i głowicy ultrasonograficznej. Celem tego badania była ocena zdolności konwulucyjnej sieci neuronowej (CNN) do klasyfikowania i rozpoznawania obrazów ultrasonograficznych stawu biodrowego uzyskanych przy prawidłowym i nieprawidłowym położeniu głowicy ultrasonograficznej we wspomaganą komputerowo diagnostyce dysplazji dziecięcej. Do badania wybrano sieci CNN, takie jak GoogleNet, SqueezeNet i AlexNet. Wykazano, że najbardziej optymalne dla tego zadania jest użycie CNN GoogleNet. Jednocześnie w CNN zastosowano metodologię uczenia transferowego. Zastosowano precyzyjne dostrajanie sieci i dodatkowe szkolenie na podstawie 97 próbek obrazów ultrasonograficznych stawu biodrowego, typ obrazu RGB 32 bity, 210 × 300 pikseli. Przeprowadzono dostrajanie dolnych warstw struktury CNN, w której zidentyfikowano 5 klas, odpowiednio 4 klasy typów dysplazji stawu biodrowego według Grafy oraz obraz ultrasonograficzny typu ERROR, w którym pozycja głowicy ultrasonograficznej i stawu biodrowego w diagnostyce ultrasonograficznej mają nieprawidłową orientację. Stwierdzono, że niezawodność szkolenia i testowania jest najwyższa dla sieci GoogleNet: podczas klasyfikacji w grupie szkoleniowej dokładność wynosi do 100%, podczas klasyfikacji w grupie testowej dokładność wynosi 84,5%.

**Słowa kluczowe:** konwulucyjne sieci neuronowe, diagnostyka komputerowa, obrazowanie ultrasonograficzne dysplazji dziecięcej

### Introduction

Statistics of hip joint disease are widespread in almost all countries of the world (2–3%), but there are significant ethnic features of its distribution. For example, the incidence of congenital malformations of the hip joint in newborns in the Scandinavian countries reaches 4%, in Germany – 2%, in the USA it is higher among the white population than in African Americans, and is 1–2% [1]. Hip dysplasia is a disease characterized by underdevelopment during embryogenesis of all elements involved in the formation of the joint: ligaments, cartilage, bone surfaces, muscles, nerve and vascular structures. Diagnosis of this disease is quite difficult, so in cases of late detection and late treatment of hip dysplasia in children develop severe irreversible morphological and functional changes in the affected limb. It is possible to diagnose malformations of the hip joint in newborns and young children on the basis of the results of clinical and ultrasound or X-ray examination. However, the radiation load of X-ray examination does not allow to use this method of examination of the hip joints in children under three months. In addition, the radiograph does not show non-ossified structures – elements of the femoral head, the roof of the acetabulum, which make up the majority of these anatomical formations in children of the first year of life. The use of the method of artificial contrast of the joint is quite difficult and dangerous for the child. Today, the ultrasound method of examination of the hip joints is actively developing. Ultrasound (US) in modern medicine is a fairly common method of diagnosis and provides diagnosis of local abnormalities and malformations of the human body degenerative and dystrophic diseases of the ligaments. Therefore, ultrasound is beginning to be actively used to detect developmental hip dysplasia. Ultrasound assessment of the hip joint has the advantage over X-ray examination in that

it, along with the image of the hip bone, also reflects cartilaginous structures, and covers the femoral head with the cartilage of the acetabulum. Another advantage of ultrasound diagnosis is that it can be done repeatedly, studying the development of hip dysplasia over time. The main methods of ultrasound assessment of the hip joint are the methods of Graf, Rosendahl, Harcke and Morin, Terjesen, Dahlstrom [8, 10–12, 17–19, 22]. However, they have a low reliability of diagnosis, because the result of diagnosis mainly depends on the qualifications of the doctor, because the study may be incorrect visualization of anatomical landmarks of the hip joint, diagnosed in the wrong position of the child, that is when the ultrasound sensor deviates from the standard position perpendicular to the body. The cartilaginous lip (limbus) is clearly visualized only if the sensor surface is perpendicular to the body. When fixing the ultrasound sensor with an inclination to the hip joint, the image of the limbus becomes blurred due to the effect of anisotropy. Failure to comply with the criteria of the standard ultrasound cut and, accordingly, the oblique direction of the ultrasound beam relative to the hip joint distortion of the image of the joint and make its assessment incorrectly [2, 17]. This makes it impossible to properly measure the angular performance. In addition, a fairly large error is made by visually determining the angles on the noisy speckle noise of the ultrasound image. Thus, the source of errors in determining the condition of the hip joint there is a lack of training of ultrasound specialists working in practical health care institutions, ignorance and misunderstanding that any, even minimal deviation from conventional research technology leads to projective distortion of the image on the sonogram, and therefore to the wrong conclusion. Therefore, one of the main ways to increase the reliability of the study of the hip joints is to create a new method and hardware and software for secondary processing of ultrasound images based on computer

technology. The aim of this study was to evaluate the ability of the convolutional neural network (CNN) to recognize and classify ultrasound imaging of the hip joint as the correct or incorrect at position of the ultrasound sensor head in the computer diagnosis of pediatric dysplasia.

## 1. Ways of CNN structure reconstruction

The method of studying the condition of the hip joints on the basis of analysis of ultrasound images and classification of hip dysplasia on their basis involves the following steps:

1. Pre-processing computer of ultrasound image of the hip joint.
2. Recognition and classification of ultrasound images of the hip joint when the obtained at the correct or incorrect position of the ultrasound sensor head in the computer diagnosis of pediatric dysplasia.
3. Identification of angles in the coronal plane of the hip joint.
4. Classification of hip dysplasia according to the results of the obtained angular indicators by the Graf's method.

The algorithm can be implemented both software and hardware [3–6]. In this study we will consider in detail the main part of this approach, namely the implementation of testing and rejection of correct ultrasound images of the hip joint, which provides a significant increase in the reliability of its diagnosis as a whole. To solve this problem, we use such a powerful tool as CNN, the task of which is to assign the input image to a certain class. The widespread use of neural networks is made possible by the large number of ready-made solutions for learning deep neural networks, including the use of modern multi-core processors, computing accelerators, and computing clusters with distributed memory. Structure CNN contain several layers, such as Convolution layers, ReLU layers, Pooling layers, and Fully connected (FC) layers. The structure CNN scheme for the tasks of the classification of ultrasound images of hip dysplasia is shown in Fig. 1. The CNN architecture may vary depending on the types and number of layers included. The types and number of layers depend on the specific application of the CNN or the data it works with. Based on the analysis, it was found that the MATLAB software platform is the best option for such studies. MATLAB – Deep Learning Toolbox™ provides a basis for the development and implementation of deep neural networks. The

connection of the layers in the convolutional neural network in script MATLAB® for the tasks of classification of ultrasound images of hip dysplasia can be performed as follows:

```
layers = [imageInputLayer([210 300 1])
convolution2dLayer(5,20)
reluLayer
maxPooling2dLayer(2,'Stride',2)
fullyConnectedLayer(10)
softmaxLayer
classificationLayer];
```

After defining the layers of CNN, it is necessary to specify training options using the 'trainingOptions' function. For example, options = trainingOptions ('sgdm'); Then, CNN is trained in the training sample using the 'trainNetwork' function. Training data, layers, and variants become input to the training function. Example, convnet = trainNetwork(data, layers, options); To perform the classification of ultrasound images of the hip joints with a size of  $210 \times 300$  pixels by the Graf's method, experimental studies were performed using such CNN's as GoogLeNet [21], SqueezeNet [9], and AlexNet [16]. The CNN's data were chosen not by chance, as they won the ImageNet Large Scale Visual Recognition Challenge (ILSVRC) in different years.

CNNs underwent a process of training on a sample of 97 ultrasound images, divided into classes by the method of Graf [2]: Type I; Type IIa, Type IIb; Type III, IV; and Type EROR. Type EROR includes ultrasound images of the hip joints, in which the cartilaginous lip (limbus) is indistinctly visualized in the case of tilting the position of the sensor surface to the body. In case of ultrasound sensor tilt:

- to the back – the contours of the lower edge of the iliac bone and the acetabulum become blurred, the thickness of the epicartilage increases;
- to the front – a more pronounced bony roof of the acetabulum, the outer bony protrusion becomes pointed;
- down – the lower edge of the iliac bone is not clearly visualized;
- to the top – the bone-cartilage border or its atypical form does not get to an ultrasonic cut, thus only back departments of an acetabulum are visualized.




Fig. 1. Detailing of the structure of CNN for the tasks of classification of ultrasound images of hip dysplasia according to the Graf

As a result of the conducted researches the work of CNN used was compared. In Fig. 2 shows the image of the hip joint at the wrong (Fig. 2a) and correct position of the ultrasonic sensor head (Fig. 2b). A sample of 97 ultrasound images is usually insufficient, but for this task can be considered representative. The study presents as an example of GoogLeNet CNN configuration and training, but the same studies were done on SqueezeNet and AlexNet CNN. Due to the large amount of material epy studs, SqueezeNet and AlexNet are not considered in the article, but their final parameters are compared.




Fig. 2. Image of the hip joint: a) the image of the hip joint in the case of the inclined position of the ultrasonic sensor head to the rear (incorrect position of the ultrasonic head sensor); b) the image of the hip joint at the correct position of the sensor of the ultrasonic head

## 2. Fine-tuning and learning of CNN on the example of GoogLeNet

GoogLeNet is a convolutional neuron network that not only shows high accuracy, but also requires relatively low computing power of the PC [21]. It was used to identify abnormalities on chest radiographs. In addition, the network has shown itself well in the task of recognizing breast cancer, which shows its effectiveness in working with medical images [23]. In this study used transfer learning CNN [24], that is, this approach involves the use of CNN GoogLeNet, which earlier was trained on one data, and then reconfigured the network and learning to solve the problems of classification of ultrasound images of hip dysplasia.

It is called fine-tuning of the network while retraining took place on the database of 97 benchmark datasets of the trained sample of ultrasonic images of the hip joint were applied. CNN GoogLeNet has the structure shown in Fig. 4, 5. CNN contains

144 layers (input and output layers) and its at structure fine-tuning for the classification of hip dysplasia images. On her you can view the structure and settings of Convolution, ReLU, MaxPooling, and Inception blocks. In Fig. 3 shows the result of fine-tuning the lower layers of the GoogLeNet CNN structure, in which 5 classes are allocated, respectively (4 classes of hip dysplasia types according to the method Graf, and the Type ERROR class described above).

Fragments of the GoogLeNet CNN structure and Convolution, ReLU, MaxPooling, and Inception settings (input layers and output layers) are shown in Fig. 4 and 5, respectively.

## 3. Training of CNN GoogLeNet

A benchmark datasets of ultrasound images of the hip joints has been prepared for the CNN training. For this purpose, we used the library of images of the hip joints, which was provided by National Pirogov Memorial Medical University. Ultrasound images of hip dysplasia were selected for the experiments and divided into 5 classes: Type I; Type IIa, IIb; Type IIc, II D; Type III, IV; by Graf, and Type\_ERROR. Quantitative indicators of the base of benchmark datasets for training and testing are presented in table 1.

As can be seen from the table, fifteen images were selected from each class for teaching and 3 for testing. During the construction of the base of benchmark datasets, 97 ultrasound images of hip joints  $210 \times 300$  pixels, RGB image type, color depth 32 bits were prepared. The process of learning CNN is shown in Fig. 6.

Before learning, the learning parameters were set, which are shown in the MATLAB script snippet:

```
miniBatchSize=10;
numImages=numel(train.Files);
maxEpochs=30;
lr=0.0004;
opts = trainingOptions('sgdm', ...
'InitialLearnRate',lr,...
'LearnRateSchedule','piecewise', ...
'LearnRateDropFactor',0.2, ...
'LearnRateDropPeriod',6, ...
'MaxEpochs',maxEpochs, ...
'MiniBatchSize',miniBatchSize, ...
'Plots','training-progress');
net=trainNetwork(train,Igraph_2,opts);
% save('trainedNetIn.mat','net')
% save('test.mat','test')
```




Fig. 3. Fragments of the lower layers of the GoogLeNet CNN structure and the results of fine-tuning






Fig. 4. Fragments of the GoogLeNet CNN structure and Convolution, ReLU, MaxPooling settings (input layers)




Fig. 5. Fragments of the GoogLeNet CNN structure and Convolution, ReLU, MaxPooling settings (output layers)

Table 1. Quantitative indicators of the base of benchmark datasets for training and testing

tbl = 5x2 table (The presence of benchmark datasets in the training sample)			ans = 5x2 table (Selection of probabilistic benchmark datasets from each class)		
	Label	Count		Label	Count
1	Type I	18	1	Type I	18
2	Type III, IV	18	2	Type III, IV	18
3	Type IIa, IIb	25	3	Type IIa, IIb	18
4	Type IIc, II D	18	4	Type IIc, II D	18
5	Type_ ERROR	18	5	Type_ ERROR	18




Fig. 6. CNN GoogLeNet learning process

$lr = 0.0004$  – the LR (learning speed) hyperparameter can significantly affect the time required for a training model. The speed of learning determines how quickly the weight coefficients of convolutional neural networks are updated. The maximum number of epochs is 30. The minimum package size for analysis is 10. Some specific learning parameters 'LearnRateDropFactor' – 0.2, 'LearnRateDropPeriod' – 6 respectively, the rate of decline in learning speed and the rate of decline of the learning period.

The parameters listed in the table Fig.6 have the following definition:

- Mini-batch accuracy in CNN training. The accuracy of the classification of the mini-batch of training data sets, which is reported during the training of CNN, corresponds to the accuracy of the specific classification of the mini-group of data sets on a given iteration. During training using the Stochastic Gradient Descent with momentum (SGDM) optimization algorithm, the algorithm groups the complete set of data into iterations. The iteration corresponds to the calculation of network gradients for each mini-batch of data sets.
- Epoch – the algorithm of the neural network is iterative; its steps are called epochs or cycles. Epoch – one iteration in the learning process, which includes the presentation of all examples of data sets from the learning set and, possibly, to check the quality of learning on a test sample. The learning process is carried out on a training sample.
- Mini-Batch loss – trends in loss and accuracy when learning on a mini-group of data sets. If the source layer is a Classification Source Level object, then the loss is an entropy cross loss for a multiclassification task with mutually exclusive classes.

- Base Learning rate – Basic learning speed. The software multiplies the norm coefficients of the rate of learning of the layers by this value.

Convolutional neural networks through the use of a special operation – the actual convolution – allows you to simultaneously reduce the amount of information stored in memory, thereby better cope with images of higher resolution. This allows you to highlight reference features of the image, such as edges, contours or borders. At the next level of processing from these edges and faces it is possible to recognize repeating fragments of textures which can further develop into fragments of the image. In essence, each layer of the neural network uses its own transformation. If on the first layers the network operates with such concepts as "edges", "borders", etc., then the concepts "texture", "parts of objects" are used further. As a result of such processing, we can correctly classify the image of a condition of a hip joint of the child. In Fig. 7 shows the so-called tile images of the input image of the hip joint of the child, which forms the first convolutional layer conv1 CNN filters with an amount of  $8 \times 8$ , size  $7 \times 7 \times 3$ .

The script of the MATLAB R2019b package for forming a tile of the state of the child's hip joint, for the first convolutional layer conv1 CNN is written below:

```
net = GoogLeNet;
im = imread(fullfile(matlabroot,'examples','nnet','60-57_300-210.jpg'));
imshow(im)
imgSize = size(im);
imgSize = imgSize(1:2);
act1 = activations(net,im,'conv1');
sz = size(act1);
act1 = reshape(act1,[sz(1) sz(2) 1 sz(3)]);
I = imtile(mat2gray(act1),'GridSize',[8 8]);
imshow(I)
```

CNN GoogLeNet on 144 layers was trained in a training sample of 97 images of hip dysplasia with learning parameters: number of epochs 30, number of iterations 210, training time 4.1 minutes, mini – batch accuracy in classification on the training group up to 100%, mini – batch loss in training on mini-group of data sets – 0.0260, basic learning speed –  $6.4 \times 10^{-7}$ , network weight after training 87,739 MB, table on the Fig. 6.

The personal computer on which the learning process took place had the following computing power:

- CPU: Intel (R) Core (TM) i7-4702MQ CPU @ 2.2GHz... 2.2GHz;
- RAM: 8.00 GB;
- GPU video adapter: GT 750M (GK107 graphics processor is equipped with 384 CUDA cores and operates at a frequency of 967 MHz (turbo mode is supported), and the width of the memory bus is 128 bits).

#### 4. Experimental research and comparison of modeling results

In order to select the best CNN for the task of recognition, classification and selection of correct ultrasound images of the hip joint, machine learning and testing of GoogLeNet, SqueezeNet and AlexNet CNNs were carried out. Characteristics of the considered CNN's are summarized in table 2.

As can be seen from table 2, reliability in training and testing on a sample of 97 images of hip dysplasia the highest for the GoogLeNet network: up to 100% for classification in the training group, 84.5% for classification in the test group. The main objective of this study was to classify ultrasound images hip joint on the correct (Type I; Type IIa, IIb; Type IIc, IID; Type III, IV; by Graf), and incorrect class Type\_ERROR, where position of the head of ultrasound sensor in ultrasound diagnostics of the hip joint are incorrect orientation to the body. In Fig. 8 shows a histogram of the comparison of the main characteristics of CNN's SqueezeNet, GoogLeNet, AlexNet.

Table 2 and the histogram show that a number of key characteristics such as the number of layers, the weight of the network after training (MB) – CNN SqueezeNet has better performance, and the accuracy in the classification of the test group (%) approaching GoogleNet. Also, in the study of CNN AlexNet found that the number of layers – 25 is not enough to achieve accuracy in the classification of the test group at least up to 80%. In the future, it is proposed to use software and hardware of artificial intelligence, which are discussed in [13,14,15], which will help improve the proposed approach and increase the speed and reliability of diagnosing ultrasound medical images of hip dysplasia.




Fig. 7. Tiles of the images of the input image of the hip joint of the child, which forms the first convolutional layer conv1 CNN filters in the amount of  $8 \times 8$ , size  $7 \times 7 \times 3$

Table 2. Characteristics of CNN's SqueezeNet, GoogLeNet and AlexNet during training and testing on a sample of 97 images of hip dysplasia

	SqueezeNet	GoogLeNet	AlexNet
Number of layers	68	144	25
Number of epochs	30	30	12
Number of iterations	270	210	216
Training time (minutes)	2.16	4.7	0.46
Accuracy in the classification of the training group (%)	up to 100%	up to 100%	up to 75%
Accuracy in the classification of the test group (%)	83	84.5	62.7
Basic learning speed (coefficient)	$6.4 \times 10^{-7}$	$6.4 \times 10^{-7}$	$8.0 \times 10^{-5}$
Network weight after training (MB)	13	87.739	68.4




Fig. 8. Comparison of the main characteristics of CNN's SqueezeNet, GoogLeNet, AlexNet

## 5. Discussion

It is possible to diagnose malformations of the hip joint in newborns and young children on the basis of the results of clinical and ultrasound or X-ray examination. Ultrasound assessment of the hip joint has the advantage over X-ray examination in that it, along with the image of the hip bone, also reflects cartilaginous structures, and covers the femoral head with the cartilage of the acetabulum. Another advantage of ultrasound diagnosis is that it can be done repeatedly, studying the development of hip dysplasia over time. The main methods of ultrasound assessment of the hip joint are the methods of Graf, Rosendahl, Harcke and Morin, Terjesen, Dahlstrom [8,10,11,12,17,18,19,22]. However, they have a low reliability of diagnosis, because the result of diagnosis mainly depends on the qualifications of the doctor, because the study may be incorrect visualization of anatomical landmarks of the hip joint, diagnosed in the wrong position of the child, that is when the sensor deviates from the standard position perpendicular to the body. The cartilaginous lip (limbus) is clearly visualized only if the sensor surface is perpendicular to the body. When fixing the sensor with an inclination to the hip joint, the image of the limbus becomes blurred due to the effect of anisotropy. Failure to comply with the criteria of the standard cut and, accordingly, the oblique direction of the ultrasound beams relative to the hip joint distortion of the image of the joint and make its assessment incorrectly [17,2]. Thus, the problem in ultrasound diagnostics hip dysplasia is the lack of experience of the doctor in case of incorrect orientation of the hip joint and ultrasound head. Therefore, the work has taken the first step towards creating an intelligent system that will predict the class of development of hip dysplasia and will filter out ultrasound images of the hip joint with incorrect diagnostics. Similar CNN-based systems are used to recognize and classify diseases in medical images [7, 20]. In the future, it is proposed to add a computer algorithm for quantitative measurement of the angles  $\alpha$  and  $\beta$  of the hip joint according to Graf's method.

## 6. Conclusion

The study proposes a computer method for classification of ultrasound images of hip dysplasia using Graf's classification. The positive possibilities of the convolutional neural network for the classification and recognition of images of the hip joint obtained at the correct or incorrect position of the ultrasound sensor head are shown. The ability of CNN to select correct ultrasound images of the hip joint, thereby improving the accuracy of diagnosing

pediatric dysplasia, has been demonstrated. With this purpose it was conducted experimental studies on GoogLeNet, SqueezeNet, and AlexNet CNNs to select the best. The CNN's data were chosen not by chance, as they won the ImageNet Large Scale Visual Recognition Challenge (ILSVRC) in different years. They were fine-tuned and trained using a database of ultrasound images of the hip joint. It was found that the reliability of training and testing on a sample of 97 images of the hip joint is the highest for the GoogLeNet network: when classified in the training group accuracy is up to 100%, when classified in the test group accuracy – 84.5%. According to the others parameters such as the number of layers, the accuracy of classification in the test group, the weight of the network after training, CNN SqueezeNet has marginally better performance. In the study of CNN AlexNet found that the number of layers of 25 is insufficient to achieve accuracy in the classification of the test group at least up to 80%.

## References

- [1] Bilynsky Y. Y., Urvan O. G., Guralnyk A. B.: Modern methods of perinatal diagnosis of hip dysplasia: global trends. Scientific Proceedings of VNTU 4, 2019, 40–50.
- [2] Bilynsky Y. Y. et al.: Overview of methods of ultrasound diagnosis of hip dysplasia and determination of the most appropriate of them for computer prediction of the disease. Medical Informatics and Engineering 3, 2019, 49–58 [http://doi.org/10.11603/mie.1996-1960.2019.3.10432].
- [3] Bilynsky Y. Y. et al.: Algorithm of computer diagnostics of 2D ultrasound images of hip dysplasia. Modern problems of information communications, radioelectronics and nanosystems. International scientific and technical conference, Vinnytsia 2019, 150–153.
- [4] Bilynsky Y. Y. et al.: Computer analysis of 2D ultrasound images of the hip joint and measurement of its geometry. Information Technologies and Computer Engineering 3(46), 2019, 4–13 [http://doi.org/10.31649/1999-9941-2019-46-3-4-14].
- [5] Bilynsky Y. Y. et al.: Contouring of microcapillary images based on sharpening to one pixel of boundary curves. Proc. SPIE 10445, 2017, 104450Y [http://doi.org/10.1117/12.2281005].
- [6] Bilynsky Y. et al.: Controlling geometric dimensions of small-size complex-shaped objects. Proc. SPIE 10445, 2017, 104450I [http://doi.org/10.1117/12.2280899].
- [7] Breve F. A.: COVID-19 detection on Chest X-ray images: A comparison of CNN architectures and ensembles. Expert Systems With Applications, 2022, [http://doi.org/10.1016/j.eswa.2022.117549].
- [8] Dahlström H.: Dynamic ultrasonic evaluation of congenital hip dislocation. University of Umeå, 1989.
- [9] Forrest N. I. et al.: SqueezeNet: Alexnet-level accuracy with 50x fewer parameters and <0.5mb model size. arXiv:1602.07360, 2016.
- [10] Graf R. et al.: Hip sonography update. Quality-management, catastrophes-tips and tricks. Medical Ultrasonography 15(4), 2013, 299–303.
- [11] Graf R.: The diagnosis of congenital hip-joint dislocation by the ultrasonic compound treatment. Arch. Orth. Traum. Surg. 97, 1980, 117–133, [http://doi.org/10.1007/BF00450934].
- [12] Harcke H. et al.: Examination of the infant hip with real-time ultrasonography. J. Ultrasound Med. 3, 1984, [http://doi.org/10.7863/jum.1984.3.3.131].



- [13] Krasilenko V. et al.: Modeling optical pattern recognition algorithms for object tracking based on nonlinear equivalent models and subtraction of frames. Proc. SPIE 9813, 2015, 981302 [http://doi.org/10.1117/12.2205779].
- [14] Krasilenko V. et al.: Design and simulation of programmable relational optoelectronic time-pulse coded processors as base elements for sorting neural networks. Proc. SPIE 7723, 2010, 77231G [http://doi.org/10.1117/12.851574].
- [15] Krasilenko V. et al.: Design and simulation of optoelectronic complementary dual neural elements for realizing a family of normalized vector 'equivalence-nonequivalence' operations. Proc. SPIE 7703, 2010, 77030P [http://doi.org/10.1117/12.850871].
- [16] Krizhevsky A. et al.: ImageNet classification with deep convolutional neural networks. Communications of the ACM 60(6), 2017, 84–90.
- [17] Marochko N. V.: Ultrasound study of hip joints in children of the first year of life: textbook for the system of post-graduate professional education of doctors. Izd. IPKSZ center, Khabarovsk 2008.
- [18] Morin C. et al.: The infant hip: real-time US assessment of acetabular development. Radiology 157, 1985, 673–677.
- [19] Rosendahl K. et al.: Developmental dysplasia of the hip: prevalence based on ultrasound diagnosis. Pediatr. Radiol. 26(9), 1996, 635–639, [http://doi.org/10.1007/BF01356824].
- [20] Shokraei F. et al.: From CNNs to GANs for cross-modality medical image estimation. Computers in Biology and Medicine 146, 2022, 105556.
- [21] Szegedy C. et al.: Going deeper with convolutions. ArXiv 2014 [http://arxiv.org/pdf/1409.4842.pdf].
- [22] Terjesen T., Bredland T., Berg V.: Ultrasound for hip assessment in the newborn. J Bone Joint Surg Br. 71(5), 1989, 767–773.
- [23] Wang D. et al.: Deep Learning for Identifying Metastatic Breast Cancer. ArXiv 2016 [http://arxiv.org/pdf/1606.05718.pdf].
- [24] Weiss K., Khoshgoftaar T. M., Wang D.: A Survey of Transfer Learning. Journal of Big Data 3(1), 2016, 1–9 [http://doi.org/10.1186/s40537-016-0043-6].

**D.Sc. Eng., Professor Yosyp Bilynsky**  
e-mail: Yosyp.bilynsky@gmail.com



Doctor of technical sciences, professor Department of General Physics of Vinnytsia National Technical University, professor Departments of Computer Sciences and Economics of Cybernetics of Vinnytsia National Agrarian University, Vinnytsia, Ukraine. Corresponding member of the Academy of Applied Electronics.  
Scientific direction: development of sensors, processing signals and images.

<http://orcid.org/0000-0002-9659-7221>

**Ph.D. Aleksandr Nikolskyy**  
e-mail: nikolskyy@i.ua



Candidat of Technical Sciences, associate professor of the Biophysics, Informatics and Medical Equipment Department of National Pirogov Memorial Medical University, Vinnytsia, Ukraine.  
Scientific direction: Neural Networks, preprocessing of medical images, Optoelectronic Structure.

<http://orcid.org/0000-0002-0098-0606>

**Ph.D. Viktor Revenok**  
e-mail: vrevenok@ukr.net



Candidat of Technical Sciences, associate professor of the Biophysics, Informatics and Medical Equipment Department of National Pirogov Memorial Medical University, Vinnytsia, Ukraine, associate professor Departments of Computer Sciences and Economics of Cybernetics of Vinnytsia National Agrarian University, Vinnytsia, Ukraine.  
Scientific direction: computer modeling of biophysical systems, preprocessing of medical images, modernization of endoscopic systems.

<http://orcid.org/0000-0002-8239-6955>

**D.Sc. Med. Vasyl Pogorilyi**  
e-mail: pogorilyi@vnm.edu.ua



Doctor of Medical Sciences, professor, Vice-rector on Scientific and Pedagogical (Medical) Work, National Pirogov Memorial Medical University, Vinnytsia, Ukraine.  
Scientific direction: prevention of children's surgery, surgical intervention technique for peritonitis, intestinal obstruction, congenital malformations, injuries, pinched hernias, treatment of purulent-inflammatory diseases of soft tissues and bones.

<http://orcid.org/0000-0001-5317-5216>

**Ph.D. Saule Smailova**  
e-mail: Saule\_Smailova@mail.ru



Saule Smailova is currently a lecturer at the Department of Information Technology, D.Serikbayev East Kazakhstan State Technical University Ust-Kamenogorsk, Al-Farabi Kazakh National University, Almaty, Kazakhstan.  
She is a co-author over 60 papers in journals, book chapters, and conference proceedings. Member of Expert Group in the Computer Science specialization of IQAA.  
Her professional interests are teaching, artificial intelligence, software engineering, data processing.

<http://orcid.org/0000-0002-8411-3584>

**Ph.D., Associate Professor Oksana Voloshina**  
e-mail: woloshina5555@gmail.com



Candidate of Pedagogic Sciences, associate professor, Vinnytsia Mykhailo Kotsubynsky State Pedagogical University, Ministry of Education and Science of Ukraine, Vinnytsia. Scientific directions: pedagogy, professional education and management of educational institutions, training of highly qualified specialists.

<http://orcid.org/0000-0002-9977-7682>

**Ph.D. Saule Kumargazhanova**  
e-mail: SKumargazhanova@gmail.com



She is currently the dean of the Department of Information Technologies and Intelligent Systems of D. Serikbayev East Kazakhstan Technical University. She is a co-author over 50 papers in journals and conference proceedings. Her professional interests are software engineering, data processing and analysis.

<http://orcid.org/0000-0002-6744-4023>